



STEFANO MARDEGAN

more than a fabric

Articolo Article	NYLON 420/POL 300 DOT RIP-STOP 4 PU WR
------------------	---

Norma Norm	Descrizione Description	Valore Values	U.M.		Tolleranza Tolerances
	Composizione Composition	43 37 20	% % %	PA PES PU	
	Spessore - Thickness	≥ 0,50	mm		
DIN EN ISO 2060	Titolo	470 NY	dTex	Ordito Warp	
	Filato	330 POL	dTex	Trama Weft	
UNI EN ISO 2286-2	Peso - Weight	290	gr/m2		+/- 5%
EN ISO 2286-1	Altezza - Width	150	cm		+/- 1
UNI 4818 PT. 6°	Resistenza alla trazione	≥ 2400	N/5cm	Ordito Warp	
	Tensile strength	≥ 1250	N/5cm	Trama Weft	
UNI 4818 PT. 6°	Allungamento a Rottura	≥ 50	%	Ordito Warp	
	Elongation at Break	≥ 50	%	Trama Weft	
UNI 4818 PT. 9°	Resistenza alla lacerazione	≥ 350	N	Ordito Warp	
	Tear strength	≥ 250	N	Trama Weft	
UNI EN ISO 105	Resistenza alla luce Colour Fastness	6	Scala blu Blu scale		
UNI 9475 CSE RF 1/75/A	Resistenza al Fuoco Fire Resistance	NO			

I valori sono indicativi - All values are given for information only

12/01/2021